

Carbide End Mills
超硬ソリッドエンドミル

レギュラー刃長 Regular
Side Cutting, Slotting, Spot Facing, Semifinishing, Finishing
外径公差 Dia.tolerance
φ0.1~φ6 : 0~-0.02
φ6.1~φ30 : 0~-0.025
h6

2枚刃
2Flutes



HES2

超硬 Carbide, 傾角30° Helix angle, 切削条件表 Cutting Conditions, A412

Table with 7 columns: Item code, Stock, Tool dia., Flute length, Overall length, Shank dia., Suggested retail price(¥). Rows include HES2001 to HES2046.

Table with 7 columns: Item code, Stock, Tool dia., Flute length, Overall length, Shank dia., Suggested retail price(¥). Rows include HES2047 to HES2092.

Table with 7 columns: Item code, Stock, Tool dia., Flute length, Overall length, Shank dia., Suggested retail price(¥). Rows include HES2093 to HES2300.

対応被削材 Applicable work material
Carbon steel, Pre-hardened steel, Hardened steel, Stainless steel, Titanium alloy, Copper alloy, Aluminum alloy

●印：標準在庫品です。 □印：特定代理店在庫です。弊社営業へお問合せください。
● : Stocked items. □ : Stocked by specified distributor. Contact with our sales department.

再研磨対応外径範囲 Re-grinding compatibility range
Item code, Outer dia. (mm), End (mm)