


- アルミニウム、銅合金専用のエンドミルです。
- アルミのドライ加工ができます。

This end mill is for Aluminum and Copper Alloy.

It's possible to dry process of Aluminum.



LIST 9330

オーダ方法 商品記号

単位 (Unit) : mm

商品記号 Code	外径 DC	刃長 APMX	全長 OAL	シャンク径 DCONMS	在庫 Stock	参考価格 (円) Price (¥)		
2DLCM1	1	3	40	4	●	4,780		
2DLCM1.1	1.1				—			
2DLCM1.2	1.2				—			
2DLCM1.3	1.3				□	—		
2DLCM1.4	1.4				—			
2DLCM1.5	1.5	4			●	4,780		
2DLCM1.6	1.6				—			
2DLCM1.7	1.7				—			
2DLCM1.8	1.8				□	—		
2DLCM1.9	1.9				—			
2DLCM2	2	5			●	4,730		
2DLCM2.1	2.1				—			
2DLCM2.2	2.2				—			
2DLCM2.3	2.3				□	—		
2DLCM2.4	2.4				—			
2DLCM2.5	2.5	6			●	4,730		
2DLCM2.6	2.6				—			
2DLCM2.7	2.7				—			
2DLCM2.8	2.8				□	—		
2DLCM2.9	2.9				—			
2DLCM3	3	8	45	6	●	4,730		
2DLCM3.1	3.1				—			
2DLCM3.2	3.2				—			
2DLCM3.3	3.3				□	—		
2DLCM3.4	3.4				—			
2DLCM3.5	3.5	10			●	5,930		
2DLCM3.6	3.6				—			
2DLCM3.7	3.7				—			
2DLCM3.8	3.8				□	—		
2DLCM3.9	3.9				—			
2DLCM4	4	11			●	5,930		
2DLCM4.1	4.1				—			
2DLCM4.2	4.2				—			
2DLCM4.3	4.3				□	—		
2DLCM4.4	4.4				—			
2DLCM4.5	4.5	13			●	6,390		
2DLCM4.6	4.6				—			
2DLCM4.7	4.7				—			
2DLCM4.8	4.8				□	—		
2DLCM4.9	4.9				—			
2DLCM5	5	16	60	8	●	6,390		
2DLCM5.1	5.1				—			
2DLCM5.2	5.2				—			
2DLCM5.3	5.3				□	—		
2DLCM5.4	5.4				—			
2DLCM5.5	5.5				●	7,250		
2DLCM5.6	5.6				—			
2DLCM5.7	5.7				—			
2DLCM5.8	5.8				□	—		
2DLCM5.9	5.9				—			
2DLCM6	6	16			60	8	●	6,650
2DLCM6.1	6.1						—	
2DLCM6.2	6.2						—	
2DLCM6.3	6.3						—	
2DLCM6.4	6.4						—	
2DLCM6.5	6.5						□	—
2DLCM6.6	6.6						—	
2DLCM6.7	6.7						—	
2DLCM6.8	6.8						—	
2DLCM6.9	6.9						—	
2DLCM7	7	16	●	7,930				
2DLCM7.1	7.1		—					
2DLCM7.2	7.2		—					
2DLCM7.3	7.3		□	—				
			—					

商品記号 Code	外径 DC	刃長 APMX	全長 OAL	シャンク径 DCONMS	在庫 Stock	参考価格 (円) Price (¥)		
2DLCM7.4	7.4	16	60	8	□	-		
2DLCM7.5	7.5					-		
2DLCM7.6	7.6					-		
2DLCM7.7	7.7					-		
2DLCM7.8	7.8					-		
2DLCM7.9	7.9	-						
2DLCM8	8	19			70	10	●	8,610
2DLCM8.1	8.1						-	
2DLCM8.2	8.2						-	
2DLCM8.3	8.3						-	
2DLCM8.4	8.4		□	-				
2DLCM8.5	8.5			-				
2DLCM8.6	8.6			-				
2DLCM8.7	8.7			-				
2DLCM8.8	8.8			-				
2DLCM8.9	8.9		-					
2DLCM9	9		22	75	12	●	10,900	
2DLCM9.1	9.1					-		
2DLCM9.2	9.2					-		
2DLCM9.3	9.3					-		
2DLCM9.4	9.4					□	-	
2DLCM9.5	9.5	-						
2DLCM9.6	9.6	-						
2DLCM9.7	9.7	-						
2DLCM9.8	9.8	-						
2DLCM9.9	9.9	-						
2DLCM10	10	26	100	20	●	10,700		
2DLCM10.1	10.1				-			
2DLCM10.2	10.2				-			
2DLCM10.3	10.3				-			
2DLCM10.4	10.4				□	-		
2DLCM10.5	10.5					-		
2DLCM10.6	10.6					-		
2DLCM10.7	10.7					-		
2DLCM10.8	10.8					-		
2DLCM10.9	10.9				-			
2DLCM11	11	32	16	20	●	14,100		
2DLCM11.1	11.1				-			
2DLCM11.2	11.2				-			
2DLCM11.3	11.3				-			
2DLCM11.4	11.4				□	-		
2DLCM11.5	11.5					-		
2DLCM11.6	11.6					-		
2DLCM11.7	11.7					-		
2DLCM11.8	11.8					-		
2DLCM11.9	11.9				-			
2DLCM12	12	38	100	20	●	14,600		
2DLCM16	16				-			
2DLCM20	20				-			

外径 DC (mm)		許容差 Tolerance (mm)	
を超え Above	以下 Up to		
	3	- 0.014 ~ - 0.028	
3	6	- 0.020 ~ - 0.038	
6	10	- 0.025 ~ - 0.047	
10		- 0.032 ~ - 0.059	

DLC コーティングは潤滑性が高く耐凝着性に優れています。

新商品

超硬ドリル

ハイスドリル

タップ

超硬
エンドミル

ハイス
エンドミル

切断工具

バック・
セット商品
その他

精密工具

技術資料
索引