


●圧倒的な流量・流速のオイルホール形状で、冷却性、潤滑性、切りくず排出性を格段に向上

The oil hole shape improves cooling, lubrication, and chip evacuation.



LIST 9866

オード方法 商品記号

商品記号 Code	直径 DC	有効長 LU	溝長 LCF	シャンク長 LS	全長 OAL	シャンク径 DCONMS	先端 PL	在庫 Stock	価格 Price (¥)
AQRVDOH5D0300	3.0	24.5	29	48	78	3	0.5	●	15,600
AQRVDOH5D0301	3.01			51.1				□	—
AQRVDOH5D0302	3.02	28.5						□	—
AQRVDOH5D0303	3.03			51.2				□	—
AQRVDOH5D0310	3.1	28.4						□	16,200
AQRVDOH5D0320	3.2	28.2	33	51.3			0.6	●	16,200
AQRVDOH5D0330	3.3	28.1		51.4				□	16,200
AQRVDOH5D0340	3.4	27.9		51.5				□	16,200
AQRVDOH5D0350	3.5	27.8		51.6	86	4		●	16,200
AQRVDOH5D0360	3.6	31.6						□	16,300
AQRVDOH5D0370	3.7	31.5		47.7				□	16,300
AQRVDOH5D0380	3.8	31.3		47.8				□	16,300
AQRVDOH5D0390	3.9	31.2	37	47.9				□	16,300
AQRVDOH5D0398	3.98							□	—
AQRVDOH5D0399	3.99	31		48			0.7	●	16,300
AQRVDOH5D0400	4.0							□	—
AQRVDOH5D0401	4.01			55.1				□	—
AQRVDOH5D0402	4.02	35						□	—
AQRVDOH5D0403	4.03			55.2				□	—
AQRVDOH5D0410	4.1	34.9						□	16,800
AQRVDOH5D0420	4.2	34.7	41	55.3				□	16,800
AQRVDOH5D0430	4.3	34.6		55.4				□	16,800
AQRVDOH5D0440	4.4	34.4		55.5				□	16,800
AQRVDOH5D0450	4.5	34.3		55.6	98	5		●	16,800
AQRVDOH5D0460	4.6	38.1						□	17,100
AQRVDOH5D0470	4.7	38						□	17,100
AQRVDOH5D0480	4.8	37.8		51.8				□	17,100
AQRVDOH5D0490	4.9	37.7	45	51.9				□	17,100
AQRVDOH5D0498	4.98							□	—
AQRVDOH5D0499	4.99	37.5		52				□	—
AQRVDOH5D0500	5.0							□	—
AQRVDOH5D0501	5.01			52.1				□	—
AQRVDOH5D0502	5.02	38.5						□	—
AQRVDOH5D0503	5.03			52.2				□	—
AQRVDOH5D0510	5.1	38.4						□	18,100
AQRVDOH5D0520	5.2	38.2	46	52.3				□	18,100
AQRVDOH5D0530	5.3	38.1		52.4				□	18,100
AQRVDOH5D0540	5.4	37.9		52.5				□	18,100
AQRVDOH5D0550	5.5	37.8		52.6	100	6	1	●	18,100
AQRVDOH5D0560	5.6	41.6						□	18,900
AQRVDOH5D0570	5.7	41.5		48.7				□	18,900
AQRVDOH5D0580	5.8	41.3		48.8				□	18,900
AQRVDOH5D0590	5.9	41.2	50	48.9				□	18,900
AQRVDOH5D0598	5.98							□	—
AQRVDOH5D0599	5.99	41		49				□	—
AQRVDOH5D0600	6.0							□	—
AQRVDOH5D0601	6.01			53.1				□	—
AQRVDOH5D0602	6.02	45						□	—
AQRVDOH5D0603	6.03			53.2				□	—
AQRVDOH5D0605	6.05	44.9						□	—
AQRVDOH5D0610	6.1							□	18,900
AQRVDOH5D0620	6.2	44.7	54	53.3				□	18,900
AQRVDOH5D0630	6.3	44.6		53.4				□	18,900
AQRVDOH5D0640	6.4	44.4		53.5				□	18,900
AQRVDOH5D0650	6.5	44.3		53.6				□	18,900
AQRVDOH5D0660	6.6	48.1		49.7				□	20,300
AQRVDOH5D0670	6.7	48						□	20,300
AQRVDOH5D0680	6.8	47.8	58	49.8				□	20,300
AQRVDOH5D0690	6.9	47.7		49.9				□	20,300
AQRVDOH5D0698	6.98	47.5	50					□	—

単位 (Unit) : mm

商品記号 Code	直径 DC	有効長 LU	溝長 LCF	シャンク長 LS	全長 OAL	シャンク径 DCONMS	先端 PL	在庫 Stock	価格 Price (¥)
AQRVDOH5D0699	6.99	47.5	58	50	109	7		□	—
AQRVDOH5D0700	7.0							●	20,300
AQRVDOH5D0701	7.01			54.1				□	—
AQRVDOH5D0702	7.02	51.5						□	—
AQRVDOH5D0703	7.03			54.2				□	—
AQRVDOH5D0705	7.05	51.4						□	—
AQRVDOH5D0710	7.1	62						□	21,200
AQRVDOH5D0720	7.2	51.2		54.3				□	21,200
AQRVDOH5D0730	7.3	51.1		54.4				□	21,200
AQRVDOH5D0740	7.4	50.9		54.5				□	21,200
AQRVDOH5D0750	7.5	50.8		54.6	118	8		●	21,200
AQRVDOH5D0760	7.6	54.6		50.7				□	22,600
AQRVDOH5D0770	7.7	54.5		50.8				□	22,600
AQRVDOH5D0780	7.8	54.3		50.9				□	22,600
AQRVDOH5D0790	7.9	54.2	66	50.9				□	22,600
AQRVDOH5D0798	7.98							□	—
AQRVDOH5D0799	7.99	54		51				□	—
AQRVDOH5D0800	8.0							□	—
AQRVDOH5D0801	8.01			55.1				□	—
AQRVDOH5D0802	8.02	58						□	—
AQRVDOH5D0803	8.03			55.2				□	—
AQRVDOH5D0805	8.05	57.9						□	—
AQRVDOH5D0810	8.1	70						□	23,700
AQRVDOH5D0820	8.2	57.7		55.3				□	23,700
AQRVDOH5D0830	8.3	57.6		55.4				□	23,700
AQRVDOH5D0840	8.4	57.4		55.5	127	9		●	23,700
AQRVDOH5D0850	8.5	57.3		55.6				□	23,700
AQRVDOH5D0860	8.6	61.1		51.7				□	25,100
AQRVDOH5D0870	8.7	61		51.8				□	25,100
AQRVDOH5D0880	8.8	60.8		51.9				□	25,100
AQRVDOH5D0890	8.9	60.7	74	51.9				□	25,100
AQRVDOH5D0898	8.98							□	—
AQRVDOH5D0899	8.99	60.5		52				□	—
AQRVDOH5D0900	9.0							□	—
AQRVDOH5D0901	9.01			56.1				□	—
AQRVDOH5D0902	9.02	64.5						□	—
AQRVDOH5D0903	9.03			56.2				□	—
AQRVDOH5D0905	9.05	64.4						□	—
AQRVDOH5D0910	9.1	78						□	—
AQRVDOH5D0920	9.2	64.2		56.3				□	26,100
AQRVDOH5D0930	9.3	64.1		56.4				□	26,100
AQRVDOH5D0940	9.4	63.9		56.5				□	26,100
AQRVDOH5D0950	9.5	63.8		56.6	136	10		●	26,100
AQRVDOH5D0960	9.6	67.6		52.7				□	26,500
AQRVDOH5D0970	9.7	67.5		52.8				□	26,500
AQRVDOH5D0980	9.8	67.3		52.9				□	26,500
AQRVDOH5D0990	9.9	67.2	82	52.9				□	26,500
AQRVDOH5D0998	9.98							□	—
AQRVDOH5D0999	9.99	67		53				□	—
AQRVDOH5D1000	10.0							□	—
AQRVDOH5D1001	10.01			60.1				□	—
AQRVDOH5D1002	10.02	72						□	—
AQRVDOH5D1003	10.03			60.2				□	—
AQRVDOH5D1005	10.05	71.9						□	—
AQRVDOH5D1010	10.1	87						□	—
AQRVDOH5D1020	10.2	71.7		60.3	149	11		●	28,000
AQRVDOH5D1030	10.3	71.6		60.4				□	28,000
AQRVDOH5D1040	10.4	71.4		60.5				□	28,000
AQRVDOH5D1050	10.5	71.3		60.6				□	28,000
AQRVDOH5D1060	10.6	75.1	91	56.7				□	29,000

新商品

超硬ドリル

ハイスドリル

タップ

超硬
エンドミル

ハイス
エンドミル

切断工具

バック・
セット商品
その他

精密工具

技術資料
索引

新商品

超硬ドリル

ハイスドリル

タップ

超硬
エンドミル

ハイス
エンドミル

切断工具

バック・
セット商品
その他

精密工具

技術資料
索引

← 前頁 Previous Page

単位 (Unit) : mm

商品記号 Code	直径 DC	有効長 LU	溝長 LCF	シャンク長 LS	全長 OAL	シャンク径 DCONMS	先端 PL	在庫 Stock	参考価格(円) Price (¥)
AQRVDOH5D1070	10.7	75		56.7			1.9		29,000
AQRVDOH5D1080	10.8	74.8		56.8			●		29,000
AQRVDOH5D1090	10.9	74.7		56.9	149	11			29,000
AQRVDOH5D1098	10.98						□		—
AQRVDOH5D1099	10.99	74.5		57					—
AQRVDOH5D1100	11.0						●		29,000
AQRVDOH5D1101	11.01			61.1			2		—
AQRVDOH5D1102	11.02	78.5							—
AQRVDOH5D1103	11.03			61.2			□		—
AQRVDOH5D1105	11.05	78.4							—
AQRVDOH5D1110	11.1			61.3					30,200
AQRVDOH5D1120	11.2	78.2		61.4					30,200
AQRVDOH5D1130	11.3	78.1		61.5					30,200
AQRVDOH5D1140	11.4	77.9		61.6	158	12	2.1	●	30,200
AQRVDOH5D1150	11.5	77.8							31,600
AQRVDOH5D1160	11.6	81.6		57.7					31,600
AQRVDOH5D1170	11.7	81.5		57.8					31,600
AQRVDOH5D1180	11.8	81.3		57.9					31,600
AQRVDOH5D1190	11.9	81.2							—
AQRVDOH5D1198	11.98						□		—
AQRVDOH5D1199	11.99	81		58					—
AQRVDOH5D1200	12.0						●		31,600
AQRVDOH5D1201	12.01			62.1					—
AQRVDOH5D1202	12.02	85					2.2	□	—
AQRVDOH5D1203	12.03			62.2					—
AQRVDOH5D1205	12.05	84.9							—
AQRVDOH5D1210	12.1			62.3					32,400
AQRVDOH5D1220	12.2	84.7		62.4					32,400
AQRVDOH5D1230	12.3	84.6		62.5					32,400
AQRVDOH5D1240	12.4	84.4		62.6	167	13			32,400
AQRVDOH5D1250	12.5	84.3							33,800
AQRVDOH5D1260	12.6	88.1		58.7			2.3		33,800
AQRVDOH5D1270	12.7	88		58.8					33,800
AQRVDOH5D1280	12.8	87.8		58.9					33,800
AQRVDOH5D1290	12.9	87.7		59					33,800
AQRVDOH5D1300	13.0	87.5		63.2					34,800
AQRVDOH5D1310	13.1	91.4		63.3			2.4		34,800
AQRVDOH5D1320	13.2	91.2		63.4					34,800
AQRVDOH5D1330	13.3	91.1		63.5					34,800
AQRVDOH5D1340	13.4	90.9		63.6					34,800
AQRVDOH5D1350	13.5	90.8			176	14			35,900
AQRVDOH5D1360	13.6	94.6		59.7					35,900
AQRVDOH5D1370	13.7	94.5		59.8			2.5	●	35,900
AQRVDOH5D1380	13.8	94.3		59.9					35,900
AQRVDOH5D1390	13.9	94.2		60					37,400
AQRVDOH5D1400	14.0	94		64.2					37,400
AQRVDOH5D1410	14.1	97.9		64.3					37,400
AQRVDOH5D1420	14.2	97.7		64.4			2.6		37,400
AQRVDOH5D1430	14.3	97.6		64.5					37,400
AQRVDOH5D1440	14.4	97.4		64.6	185	15			38,000
AQRVDOH5D1450	14.5	97.3							38,000
AQRVDOH5D1460	14.6	102.1		59.7					38,000
AQRVDOH5D1470	14.7	102		59.8					38,000
AQRVDOH5D1480	14.8	101.8		59.9			2.7		38,000
AQRVDOH5D1490	14.9	101.7		60					39,300
AQRVDOH5D1500	15.0	101.5		64.2					39,300
AQRVDOH5D1510	15.1	105.4		64.3					39,300
AQRVDOH5D1520	15.2	105.2		64.4	194	16	2.8		39,300
AQRVDOH5D1530	15.3	105.1		64.5					39,300
AQRVDOH5D1540	15.4	104.9							39,300

商品記号 Code	直径 DC	有効長 LU	溝長 LCF	シャンク長 LS	全長 OAL	シャンク径 DCONMS	先端 PL	在庫 Stock	参考価格(円) Price (¥)
AQRVDOH5D1550	15.5	104.8	128	64.6			2.8		39,300
AQRVDOH5D1560	15.6	108.6		60.7	194	16			40,600
AQRVDOH5D1570	15.7	108.5		60.8			2.9	●	40,600
AQRVDOH5D1580	15.8	108.3	132	60.9					40,600
AQRVDOH5D1590	15.9	108.2		61					40,600
AQRVDOH5D1600	16.0	108							40,600

一般 構造用鋼	炭素鋼	合金鋼 調質鋼	ダイス鋼 プリハードン鋼	高硬度鋼	
SS400	S45C S50C	SCM NAK	30 ~ 40 HRC	40 ~ 50 HRC	50 ~ 65 HRC
◎	◎	◎	◎	◎	— ※
ステンレス鋼		Ti 合金 耐熱合金	鋳鉄	アルミ合金	銅合金
SUS304 SUS316	SUS420	Ti / Ni Alloy	FC / FCD	AC / ADC	Cu
◎	◎	○	◎	○	○

◎:最適 Excellent ○:適用 Good ×:不適 Not Used —:推奨しません Not recommended
※硬さ 50 ~ 57HRC は○