


●アルミ合金、高シリコンアルミ、高分子材料
(CFRP、GFRP) の長寿命加工に最適です。

This drill coated 100% pure diamond is most suitable for long life drilling of Aluminum Alloy, High Silicon Aluminum Alloy and FRP.



2レーキ



新商品

オーダ方法 商品記号

単位 (Unit) : mm

商品記号 Code	直径 DC	有効長 LU	溝長 LCF	全長 OAL	先端 PL	在庫 Stock
DCD0.4	0.4	3.5	4.1	30.1	0.1	
DCD0.45	0.45	4.4	5.1			
DCD0.5	0.5	4.5	5.2			
DCD0.55	0.55	5.4		30.2	0.2	
DCD0.6	0.6	5.3				
DCD0.65	0.65	5.2				
DCD0.7	0.7	9.1				
DCD0.75	0.75	9.1				
DCD0.8	0.8	9		40.2		
DCD0.85	0.85	9				
DCD0.9	0.9	8.9				
DCD0.95	0.95	8.9				
DCD1.0	1.0	8.8		40.3	0.3	
DCD1.05	1.05	8.7				
DCD1.1	1.1	8.6				
DCD1.15	1.15	10.5				
DCD1.2	1.2	10.4				
DCD1.25	1.25	10.5				
DCD1.3	1.3	10.4		40.4	0.4	
DCD1.35	1.35	10.3				
DCD1.4	1.4	10.2				
DCD1.45	1.45	10.2				
DCD1.5	1.5	10.3				
DCD1.55	1.55	13.2				
DCD1.6	1.6	13.1				
DCD1.65	1.65	13		40.5	0.5	
DCD1.7	1.7	12.8				
DCD1.75	1.75	12.9				
DCD1.8	1.8	12.8				
DCD1.85	1.85	17.7				
DCD1.9	1.9	17.6		40.6	0.6	
DCD1.95	1.95	17.5				
DCD2.0	2.0	17.4				
DCD2.05	2.05	17.4		45.6		
DCD2.1	2.1	17.3				
DCD2.15	2.15	17.2				
DCD2.2	2.2	17.1				
DCD2.25	2.25	17				
DCD2.3	2.3	17		45.7	0.7	
DCD2.35	2.35	16.9				
DCD2.4	2.4	16.8				
DCD2.45	2.45	16.7				
DCD2.5	2.5	16.6				
DCD2.55	2.55	16.5				
DCD2.6	2.6	16.4				
DCD2.65	2.65	16.3		45.8	0.8	
DCD2.7	2.7	16.2				
DCD2.75	2.75	16.1				
DCD2.8	2.8	16				
DCD2.85	2.85	16				
DCD2.9	2.9	16				
DCD2.95	2.95	16		45.9	0.9	
DCD3.0	3.0	16				
DCD3.05	3.05	16				
DCD3.1	3.1	16		55.9		
DCD3.15	3.15	16				
DCD3.2	3.2	16				
DCD3.25	3.25	16				
DCD3.3	3.3	16		56	1	
DCD3.35	3.35	16				

商品記号 Code	直径 DC	有効長 LU	溝長 LCF	全長 OAL	先端 PL	在庫 Stock
DCD3.4	3.4	20.9		56	1	
DCD3.45	3.45	20.8				
DCD3.5	3.5	20.9				
DCD3.55	3.55	20.8				
DCD3.6	3.6	20.7				
DCD3.65	3.65	20.6		56.1	1.1	
DCD3.7	3.7	20.5				
DCD3.75	3.75	20.4				
DCD3.8	3.8	20.3				
DCD3.85	3.85	20.2				
DCD3.9	3.9	20.1		56.2	1.2	
DCD3.95	3.95	20				
DCD4.0	4.0	25.1		66.2		
DCD4.05	4.05	25				
DCD4.1	4.1	24.9				
DCD4.15	4.15	24.8				
DCD4.2	4.2	24.7				
DCD4.25	4.25	24.6		66.3	1.3	
DCD4.3	4.3	24.5				
DCD4.35	4.35	24.4				
DCD4.4	4.4	24.3				
DCD4.45	4.45	24.2				
DCD4.5	4.5	24.1				
DCD4.55	4.55	24		66.4	1.4	
DCD4.6	4.6	23.9				
DCD4.65	4.65	23.8				
DCD4.7	4.7	23.7				
DCD4.75	4.75	23.6				
DCD4.8	4.8	23.5				
DCD4.85	4.85	23.4				
DCD4.9	4.9	23.3				
DCD4.95	4.95	23.2		66.5	1.5	
DCD5.0	5.0	23.1				
DCD5.05	5.05	23				
DCD5.1	5.1	22.9				
DCD5.15	5.15	22.8				
DCD5.2	5.2	22.7				
DCD5.25	5.25	22.6		66.6	1.6	
DCD5.3	5.3	22.5				
DCD5.35	5.35	22.4				
DCD5.4	5.4	22.3				
DCD5.45	5.45	22.2		71.6		
DCD5.5	5.5	22.1				
DCD5.55	5.55	22				
DCD5.6	5.6	21.9				
DCD5.65	5.65	21.8				
DCD5.7	5.7	21.7				
DCD5.75	5.75	21.6				
DCD5.8	5.8	21.5				
DCD5.85	5.85	21.4				
DCD5.9	5.9	21.3				
DCD5.95	5.95	21.2		71.8	1.8	
DCD6.0	6.0	21.1				
DCD6.1	6.1	21				
DCD6.2	6.2	20.9				
DCD6.3	6.3	20.8				
DCD6.4	6.4	20.7				
DCD6.5	6.5	20.6				
DCD6.6	6.6	20.5		77	2	
DCD6.7	6.7	20.4				

超硬ドリル

ハイスドリル

タップ

超硬

エンドミル

ハイス

エンドミル

切断工具

バック・

セット商品

その他

精密工具

技術資料

索引

新商品

超硬ドリル

ハイスドリル

タップ

超硬
エンドミル

ハイス
エンドミル

切断工具

バック・
セット商品
その他

精密工具

技術資料
索引

← 前頁 Previous Page

商品記号 Code	直径 DC	有効長 LU	溝長 LCF	全長 OAL	先端 PL	在庫 Stock
DCD6.8	6.8	31.8	42	77	2	□
DCD6.9	6.9		42.1	77.1	2.1	
DCD7.0	7.0	31.6				
DCD7.1	7.1	36.5	47.1	82.1		
DCD7.2	7.2	36.4				
DCD7.3	7.3	36.3	47.2	82.2	2.2	
DCD7.4	7.4	36.1				
DCD7.5	7.5					
DCD7.6	7.6	35.9	47.3	82.3	2.3	
DCD7.7	7.7	35.8				
DCD7.8	7.8	35.6				
DCD7.9	7.9			82.4	2.4	
DCD8.0	8.0	35.4	47.4	87.4		
DCD8.1	8.1	35.3				
DCD8.2	8.2	35.2				
DCD8.3	8.3	35.1	47.5	87.5	2.5	
DCD8.4	8.4	34.9				
DCD8.5	8.5					
DCD8.6	8.6	34.7	47.6	87.6	2.6	
DCD8.7	8.7	34.6				
DCD8.8	8.8	34.4				
DCD8.9	8.9		47.7	87.7	2.7	
DCD9.0	9.0	34.2	52.7	92.7		
DCD9.1	9.1	39.1				
DCD9.2	9.2	39				
DCD9.3	9.3	38.9	52.8	92.8	2.8	
DCD9.4	9.4	38.7				
DCD9.5	9.5					
DCD9.6	9.6	38.5	52.9	92.9	2.9	
DCD9.7	9.7	38.4				
DCD9.8	9.8	38.2				
DCD9.9	9.9	38	53	93	3	
DCD10.0	10.0					
DCD10.1	10.1	42.9	58	98		
DCD10.2	10.2	42.8				
DCD10.3	10.3	42.7	58.1	98.1	3.1	
DCD10.4	10.4	42.5				
DCD10.5	10.5					
DCD10.6	10.6	42.3	58.2	98.2	3.2	
DCD10.7	10.7	42.2				
DCD10.8	10.8	42				
DCD10.9	10.9		58.3	98.3	3.3	
DCD11.0	11.0	41.8	63.3	103.3		
DCD11.1	11.1	46.7				
DCD11.2	11.2	46.6				
DCD11.3	11.3	46.5	63.4	103.4	3.4	
DCD11.4	11.4	46.3				
DCD11.5	11.5					
DCD11.6	11.6	46.1	63.5	103.5	3.5	
DCD11.7	11.7	46				
DCD11.8	11.8	45.8				
DCD11.9	11.9					
DCD12.0	12.0	45.6	63.6	103.6	3.6	
DCD12.1	12.1	45.5				
DCD12.2	12.2	45.4				
DCD12.3	12.3	45.3	63.7	103.7	3.7	
DCD12.4	12.4	45.1				
DCD12.5	12.5					
DCD12.6	12.6	44.9	63.8	103.8	3.8	
DCD12.7	12.7	44.8				

単位 (Unit) : mm

商品記号 Code	直径 DC	有効長 LU	溝長 LCF	全長 OAL	先端 PL	在庫 Stock
DCD12.8	12.8	44.6	63.8	103.8	3.8	□
DCD12.9	12.9		63.9	103.9	3.9	
DCD13.0	13.0	44.4				

直径 Drill Dia. (mm)		許容差 Tolerance (mm)
を超え Above	以下 Up to	
	0.95	0 ~ -0.014
0.95	3.00	0 ~ -0.020
3.00	6.00	0 ~ -0.022
6.00	10.00	0 ~ -0.025
10.00	13.00	0 ~ -0.028