


●汎用コーティングコバルトドリルです。

This is general coated cobalt HSS drills having jobbers length.



新商品

オーダ方法 GCOSD 直径

単位 (Unit) : mm

直径 DC	溝長 ℓ	全長 LF	先端 PL	在庫 Stock
1.0	12	34		
1.01				
1.02				
1.03				
1.04				
1.05				
1.06		36		
1.07				
1.08				
1.09				
1.1				
1.11	13		0.2	
1.12				
1.13				
1.14				
1.15				
1.16				
1.17				
1.18				
1.19				
1.2		38		
1.21				
1.22				
1.23				
1.24	14			
1.25				
1.26				
1.27				
1.28				
1.29				
1.3				□
1.31				
1.32				
1.33				
1.34				
1.35				
1.36				
1.37				
1.38				
1.39				
1.4	15	40	0.3	
1.41				
1.42				
1.43				
1.44				
1.45				
1.46				
1.47				
1.48				
1.49				
1.5				
1.51				
1.52				
1.53				
1.54				
1.55	16	43		
1.56				
1.57				
1.58				
1.59				

直径 DC	溝長 ℓ	全長 LF	先端 PL	在庫 Stock
1.6				
1.61				
1.62				
1.63				
1.64				
1.65	16	43	0.3	
1.66				
1.67				
1.68				
1.69				
1.7				
1.71				
1.72				
1.73				
1.74				
1.75				
1.76				
1.77				
1.78				
1.79				
1.8	18	46		
1.81				
1.82				
1.83				
1.84				
1.85				
1.86				
1.87				
1.88				
1.89				□
1.9				
1.91				
1.92				
1.93				
1.94				
1.95		49	0.4	
1.96				
1.97				
1.98				
1.99				
2.0				
2.01				
2.02				
2.03				
2.04	19			
2.05				
2.06				
2.07				
2.08				
2.09				
2.1		55		
2.11				
2.12				
2.13				
2.14				
2.15				
2.16				
2.17				
2.18			0.5	
2.19				

直径 DC	溝長 ℓ	全長 LF	先端 PL	在庫 Stock
2.2				
2.21				
2.22				
2.23				
2.24				
2.25				
2.26				
2.27				
2.28				
2.29	21	58		
2.3				
2.31				
2.32				
2.33				
2.34				
2.35				
2.36				
2.37				
2.38				
2.39				
2.4				
2.41				
2.42			0.5	
2.43				
2.44				
2.45				
2.46	23	61		
2.47				
2.48				
2.49				□
2.5				
2.51				
2.52				
2.53				
2.54				
2.55				
2.56				
2.57				
2.58				
2.59				
2.6				
2.61				
2.62	24	64		
2.63				
2.64				
2.65				
2.66				
2.67				
2.68				
2.69				
2.7				
2.71				
2.72			0.6	
2.73				
2.74				
2.75	25	67		
2.76				
2.77				
2.78				
2.79				

直径 DC	溝長 ℓ	全長 LF	先端 PL	在庫 Stock
2.8				
2.81				
2.82				
2.83	25	67		
2.84				
2.85				
2.86				
2.87				
2.88				
2.89				
2.9				
2.91				
2.92				
2.93				
2.94				
2.95				
2.96			0.6	
2.97				
2.98				
2.99				
3.0				
3.01				
3.02				
3.03				
3.04				
3.05				
3.06				
3.07	27	71		
3.08				
3.09				□
3.1				
3.11				
3.12				
3.13				
3.14				
3.15				
3.16				
3.17				
3.18				
3.19				
3.2				
3.21				
3.22				
3.23				
3.24				
3.25				
3.26				
3.27			0.7	
3.28				
3.29				
3.3				
3.31				
3.32				
3.33	29	73		
3.34				
3.35				
3.36				
3.37				
3.38				
3.39				

超硬ドリル

ハイスドリル

タップ

超硬
エンドミルハイス
エンドミル

切断工具

バック・
セット商品
その他

精密工具

技術資料
索引

← 前頁 Previous Page

単位 (Unit) : mm

新商品

超硬ドリル

ハイスドリル

タップ

超硬
エンドミルハイス
エンドミル

切断工具

バック・
セット商品
その他

精密工具

技術資料
索引

直径 DC	溝長 ℓ	全長 LF	先端 PL	在庫 Stock
3.4				
3.41				
3.42				
3.43				
3.44				
3.45				
3.46				
3.47				
3.48				
3.49	29	73		
3.5			0.7	
3.51				
3.52				
3.53				
3.54				
3.55				
3.56				
3.57				
3.58				
3.59				
3.6				
3.61				
3.62				
3.63				
3.64				
3.65				
3.66				
3.67				
3.68				
3.69				
3.7	31	76		
3.71				
3.72				
3.73				
3.74				
3.75				
3.76				
3.77				
3.78				
3.79				
3.8				
3.81			0.8	
3.82				
3.83				
3.84				
3.85				
3.86				
3.87				
3.89				
3.9	33	79		
3.91				
3.92				
3.93				
3.94				
3.95				
3.96				
3.97				
3.98				
3.99				
4.0				
4.05				
4.1				
4.15	35	83		
4.2			0.9	
4.25				
4.3				
4.35				
4.4				
4.45	36	86		
4.5				

直径 DC	溝長 ℓ	全長 LF	先端 PL	在庫 Stock
4.55			0.9	
4.6	36	86		
4.65				
4.7				
4.75	38	89		
4.8			1	
4.85				
4.9				
4.95				
5.0	40	92		
5.05				
5.1				
5.15				
5.2				
5.25				
5.3			1.1	
5.35	42	95		
5.4				
5.45				
5.5				
5.55				
5.6				
5.65				
5.7				
5.75	44	98		
5.8			1.2	
5.85				
5.9				
5.95				
6.0				
6.05				
6.1				
6.15	46	102		
6.2			1.3	
6.25				
6.3				
6.35				
6.4				
6.45				
6.5				
6.55				
6.6				
6.65				
6.7	47	105		
6.75			1.4	
6.8				
6.85				
6.9				
6.95				
7.0				
7.05				
7.1				
7.15	49	108		
7.2			1.5	
7.25				
7.3				
7.35				
7.4				
7.45				
7.5	51	111		
7.55				
7.6				
7.65				
7.7			1.6	
7.75				
7.8				
7.85	53	114		
7.9				
7.95				
8.0			1.7	

直径 DC	溝長 ℓ	全長 LF	先端 PL	在庫 Stock
8.05				
8.1				
8.15	55	117	1.7	
8.2				
8.25				
8.3				
8.35				
8.4				
8.45				
8.5	57	121	1.8	
8.55				
8.6				
8.65				
8.7				
8.75				
8.8				
8.85				
8.9	58	124	1.9	
8.95				
9.0				
9.05				
9.1				
9.15				
9.2				
9.25				
9.3				
9.35	60	127		
9.4				
9.45				
9.5				
9.55				
9.6				
9.65			2	
9.7				
9.75				
9.8	62	130		
9.85				
9.9				
9.95				
10.0				
10.05				
10.1			2.1	
10.15				
10.2				
10.25	64	133		
10.3				
10.35				
10.4				
10.45				
10.5			2.2	
10.55	65	137		
10.6				
10.65				
10.7				

直径 DC	溝長 ℓ	全長 LF	先端 PL	在庫 Stock
10.75				
10.8			2.2	
10.85				
10.9	67	140		
10.95				
11.0				
11.05			2.3	
11.1				
11.15	69	143		
11.2				
11.25				
11.3				
11.35				
11.4				
11.45				
11.5				
11.55			2.4	
11.6	71	146		
11.65				
11.7				
11.75				
11.8				
11.85				
11.9				
11.95				
12.0				
12.05	72	149	2.5	
12.1				
12.15				
12.2				
12.25				
12.3				
12.35				
12.4				
12.45				
12.5				
12.55			2.6	
12.6	74	152		
12.65				
12.7				
12.75				
12.8				
12.85				
12.9			2.7	
12.95				
13.0				

一般 構造用鋼	炭素鋼	合金鋼 調質鋼	ダイス鋼 プリハードン鋼	高硬度鋼	
SS400	S45C S50C	SCM NAK	30 ~ 40 HRC	40 ~ 50 HRC	50 ~ 65HRC
◎	◎	◎	○	×	×
ステンレス鋼		Ti 合金 耐熱合金	鋳鉄	アルミ合金	銅合金
SUS304 SUS316	SUS420	Ti / Ni Alloy	FC / FCD	AC / ADC	Cu
○	○	—	○	○	○

◎:最適 Excellent ○:適用 Good ×:不適 Not Used —:推奨しません Not recommended