



新商品

オーダ方法 **KLE** 直径 × 全長

単位 (Unit) : mm

直径 DC	全長 LF	溝長 ℓ	先端 PL	在庫 Stock
2.0	200	150	0.6	□
2.5	200		0.8	
2.5	250	175		
3.0	200	150		
3.0	250	175	0.9	□
3.0	300	200		
3.5	200	150		
3.5	250	175	1.1	
3.5	300	200		□
4.0	250	175		
4.0	300	200	1.2	
4.0	350	225		
4.0	400	250		
4.5	250	175		□
4.5	300	200	1.4	
4.5	350	225		
4.5	400	250		
5.0	300	200		□
5.0	350	225	1.5	
5.0	400	250		
5.0	450	300		
5.0	500	325		□
5.5	300	200		
5.5	350	225	1.7	
5.5	400	250		
5.5	450	300		
5.5	500	325		□
6.0	350	225	1.8	
6.0	400	250		
6.0	450	300		
6.0	500	325		
6.5	350	225		□
6.5	400	250	2	
6.5	450	300		
6.5	500	325		
7.0	350	225		□
7.0	400	250	2.1	
7.0	450	300		
7.0	500	325		
7.5	350	225		□
7.5	400	250	2.3	
7.5	450	300		
7.5	500	325		
8.0	350	225		□
8.0	400	250	2.4	
8.0	450	300		
8.0	500	325		
8.5	350	225		□
8.5	400	250	2.6	
8.5	450	300		
8.5	500	325		
9.0	350	225		□
9.0	400	250	2.7	
9.0	450	300		
9.0	500	325		
9.5	350	225		□
9.5	400	250	2.9	
9.5	450	300		
9.5	500	325		
10.0	350	225		□
10.0	400	250	3	

直径 DC	全長 LF	溝長 ℓ	先端 PL	在庫 Stock
10.0	450	300	3	□
10.0	500	325		
10.5	350	225		
10.5	400	250	3.2	
10.5	450	300		□
10.5	500	325		
11.0	350	225		
11.0	400	250	3.3	
11.0	450	300		□
11.0	500	325		
11.5	350	225		
11.5	400	250	3.5	
11.5	450	300		□
11.5	500	325		
12.0	350	225		
12.0	400	250	3.6	
12.0	450	300		□
12.0	500	325		
12.5	350	225		
12.5	400	250	3.8	
12.5	450	300		□
12.5	500	325		
13.0	350	225		
13.0	400	250	3.9	
13.0	450	300		□
13.0	500	325		

超硬ドリル

ハイスドリル

タップ

超硬
エンドミル

ハイス
エンドミル

切断工具

バック・
セット商品
その他

精密工具

技術資料
索引